


# 环保物料

Pin数	尺寸A	尺寸B
4	7.50	10.00
5	10.00	12.50
6	12.50	15.00
7	15.00	17.50
8	17.50	20.00
9	20.00	22.50
10	22.50	25.00
11	25.00	27.50
12	27.50	30.00
13	30.00	32.50
14	32.50	35.00
15	35.00	37.50
16	37.50	40.00
17	40.00	42.50
18	42.50	45.00
19	45.00	47.50
20	47.50	50.00
21	50.00	52.50
22	52.50	55.00
23	55.00	57.50
24	57.50	60.00
25	60.00	62.50
26	62.50	65.00
27	65.00	67.50



P. C. B LAYOUT

## 技术参数 SPECIFICATIONS

- ◆间距: 2.5 Pitch:2.5
- ◆适用线规: AWG#22-#28  
Applicable Wire:AWG#22-#28
- ◆额定电压: AC, DC, 250V (有效值)  
Voltage rating: AC, DC, 250V(rms)
- ◆额定电流: 2.5A, AC, DC (AWG#22)  
Current rating:2.5A, AC, DC (AWG#22)
- ◆耐压值: 800V AC/minute  
Withstand voltage:800V AC/minute
- ◆工作温度: -25℃~+85℃  
Working Temp:-25℃~+85℃
- ◆绝缘电阻: ≥1000MΩ  
Insulation resistance:≥1000MΩ
- ◆接触电阻: ≤10mΩ  
Contact resistance:≤10mΩ

## 材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-V0  
Insulator:Nylon66 UL94-V0

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD		PART. NO: XHS-B	
				LINEAR	ANGLES	APPROVED			公司网址: www.dgoonne.cn 公司电话: 0769-85337533 销售热线: 2850175986@qq.com 公司传真: 0769-85392827		DWG. NO:	
A0	新图面发行		2018.12.06	UNIT: MM	0.00±0.15	DESIGNER			TITLE: 2.50mm pitch Single Wafer		REV: A0 SHEET: 1/1	
REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	DRAWN	肖丽娟	2018.12.06				