




# 环保物料

Pin数	尺寸A	尺寸B
4	7.50	10.70
5	10.00	13.20
6	12.50	15.70
7	15.00	18.20
8	17.50	20.70
9	20.00	23.20
10	22.50	25.70
11	25.00	28.20
12	27.50	30.70
13	30.00	33.20
14	32.50	35.70
15	35.00	38.20
16	37.50	40.70
17	40.00	43.20
18	42.50	45.70
19	45.00	48.20
20	47.50	50.70
21	50.00	53.20
22	52.50	55.70
23	55.00	58.20
24	57.50	60.70
25	60.00	63.20
26	62.50	65.70
27	65.00	68.20



## 技术参数 SPECIFICATIONS

- ◆间距: 2.5 Pitch:2.5
- ◆适用线规: AWG#22-#30  
Applicable Wire:AWG#22-#30
- ◆额定电压: AC,DC, 250V (有效值)  
Voltage rating: AC, DC, 250V (rms)
- ◆额定电流: 3A, AC, DC (AWG#22)  
Current rating:3A, AC, DC (AWG#22)
- ◆耐压值: 1000V AC/minute  
Withstand voltage:1000V AC/minute
- ◆工作温度: -25℃~+85℃  
Working Temp:-25℃~+85℃
- ◆绝缘电阻: ≥1000MΩ  
Insulation resistance:≥1000MΩ
- ◆接触电阻: ≤0.02mΩ  
Contact resistance:≤0.02mΩ

## 材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-V0  
Insulator:Nylon66 UL94-V0

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	<b>东莞市康导新能源科技有限公司</b> DONGGUANG ED NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮箱: 2850175986@qq.com 公司传真: 0769-85392827		PART. NO: XHS-B
						APPROVED					DWG. NO:
A0		新图面发行		2018.12.06	UNIT: MM	DESIGNER			TITLE: 2.50mm pitch Single Housing		REV: A0
REV.		REVISION RECORD		DATE	SIZE: A4	DRAWN	肖丽娟	2018.12.06			SHEET: 1/1