



环保物料

Pin数	尺寸A	尺寸B
2	2.50	5.2
3	5.0	7.7
4	7.5	10.2
5	10.0	12.7
6	12.5	15.2
7	15.0	17.7
8	17.5	20.2
9	20.0	22.7
10	22.5	25.2
11	25.0	27.7
12	27.5	30.2



技术参数 SPECIFICATIONS

- ◆间距: 2.5 Pitch:2.5
- ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
- ◆额定电压: AC,DC, 250V (有效值)
Voltage rating: AC,DC, 250V(rms)
- ◆额定电流: 3.0A, AC, DC (AWG#22)
Current rating:3.0A, AC, DC (AWG#22)
- ◆耐压值: 1000V AC/minute
Withstand voltage:1000V AC/minute
- ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻: ≥1000MΩ
Insulation resistance:≥1000MΩ
- ◆接触电阻: ≤0.02mΩ
Contact resistance:≤0.02mΩ
- 适用印制板厚度: 1.6mm
Applicable PC board thickness:1.6mm

材料 MATERIAL

- ◆外壳: 尼龙66
Housing:Nylon66
- ◆针座: 尼龙66
Pin header:Nylon66
- ◆插针: 黄铜
Pin:Brass
- ◆端子: 磷青铜
Terminal:Phosphor bronze

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG ED NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮箱: 2850175986@qq.com 公司传真: 0769-85392827		PART. NO:	S11-NAW		
				LINEAR: 0.0±0.25 ANGLES: X° REF±6°		APPROVED					DWG. NO:			
A0	新图面发行		2018.12.06	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER			TITLE:		2.50mm pitch Single Wafer		
REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.06			REV:	A0	SHEET: 1/1