

环保物料

针座 <A>
PIN HEADER



美尚美间距条形连接器
M S M Pitch Bar Connector

技术参数 SPECIFICATIONS

间距: 2.54 Pitch:2.54
适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
额定电压: AC, DC, 100V (有效值)
Voltage rating: AC, DC, 100V(rms)
额定电流: 3.0A, AC, DC
Current rating:3.0A, AC, DC
耐压值: 800V AC/minute
Withstand voltage:800V AC/minute
工作温度 : -25℃~+85℃
Working Temp:-25℃~+85℃
绝缘电阻 : ≥1000MΩ
Insulation resistance:≥1000MΩ
接触电阻: ≤20mΩ
Contact resistance:≤20mΩ

材料 MATERIAL

外壳: 尼龙66 UL94V-0
针座: PBT

1. 基座: 尼龙66 UL94V-0
2. 插针: 磷青铜
3. 端子: 磷青铜



GENERAL TOLERANCES	
LINEAR	ANGLES
0.0±0.25	X° REF±6°
0.00±0.15	X° ±3°
0.000±0.08	X° X'±2°

SCALE: 1:1	NAME	DATE
APPROVED		
DESIGNER		
DRAWN 肖丽娟		2018.12.10

 **东莞市康导新能源科技有限公司**
DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD
公司地址: www.dgkonne.cn 公司电话: 0769-85337633
邮箱: 2850175988@qq.com 公司传真: 0769-85392827

PART. NO:	M S M-2A	
DWG. NO:		
REV:	A0	SHEET: 1/1

REV.	A0	新图面发行	2018.12.10	UNIT: MM	SIZE: A4
REV.		REVISION RECORD	DATE	SIZE: A4	

TITLE:
2.54mm pitch Single Wafer