

1		2		3		4		5		6		7		8																																																																																																																																																										
ROHS														For reference only																																																																																																																																																										
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>1.68</td></tr><tr><td>2</td><td>1.27</td><td>2.95</td></tr><tr><td>3</td><td>2.54</td><td>4.22</td></tr><tr><td>4</td><td>3.81</td><td>5.49</td></tr><tr><td>5</td><td>5.08</td><td>6.76</td></tr><tr><td>6</td><td>6.35</td><td>8.03</td></tr><tr><td>7</td><td>7.62</td><td>9.30</td></tr><tr><td>8</td><td>8.89</td><td>10.57</td></tr><tr><td>9</td><td>10.16</td><td>11.84</td></tr><tr><td>10</td><td>11.43</td><td>13.11</td></tr><tr><td>11</td><td>12.70</td><td>14.38</td></tr><tr><td>12</td><td>13.97</td><td>15.65</td></tr><tr><td>13</td><td>15.24</td><td>16.92</td></tr><tr><td>14</td><td>16.51</td><td>18.19</td></tr><tr><td>15</td><td>17.78</td><td>19.46</td></tr><tr><td>16</td><td>19.05</td><td>20.73</td></tr><tr><td>17</td><td>20.32</td><td>22.00</td></tr><tr><td>18</td><td>21.59</td><td>23.27</td></tr><tr><td>19</td><td>22.86</td><td>24.54</td></tr><tr><td>20</td><td>24.13</td><td>25.81</td></tr><tr><td>21</td><td>25.40</td><td>27.08</td></tr><tr><td>22</td><td>26.67</td><td>28.35</td></tr><tr><td>23</td><td>27.94</td><td>29.62</td></tr><tr><td>24</td><td>29.21</td><td>30.89</td></tr><tr><td>25</td><td>30.48</td><td>32.16</td></tr><tr><td>26</td><td>31.75</td><td>33.43</td></tr><tr><td>27</td><td>33.02</td><td>34.70</td></tr><tr><td>28</td><td>34.29</td><td>35.97</td></tr><tr><td>29</td><td>35.56</td><td>37.24</td></tr><tr><td>30</td><td>36.83</td><td>38.51</td></tr><tr><td>31</td><td>38.10</td><td>39.78</td></tr><tr><td>32</td><td>39.37</td><td>41.05</td></tr><tr><td>33</td><td>40.64</td><td>42.32</td></tr><tr><td>34</td><td>41.91</td><td>43.59</td></tr><tr><td>35</td><td>43.18</td><td>44.86</td></tr><tr><td>36</td><td>44.45</td><td>46.13</td></tr><tr><td>37</td><td>45.72</td><td>47.40</td></tr><tr><td>38</td><td>46.99</td><td>48.67</td></tr><tr><td>39</td><td>48.26</td><td>49.94</td></tr><tr><td>40</td><td>49.53</td><td>51.21</td></tr><tr><td>41</td><td>50.80</td><td>52.48</td></tr><tr><td>42</td><td>52.07</td><td>53.75</td></tr><tr><td>43</td><td>53.34</td><td>55.02</td></tr><tr><td>44</td><td>54.61</td><td>56.29</td></tr><tr><td>45</td><td>55.88</td><td>57.56</td></tr><tr><td>46</td><td>57.15</td><td>58.83</td></tr><tr><td>47</td><td>58.42</td><td>60.10</td></tr><tr><td>48</td><td>59.69</td><td>61.37</td></tr><tr><td>49</td><td>60.96</td><td>62.64</td></tr><tr><td>50</td><td>62.23</td><td>63.91</td></tr></table>												Pin数	尺寸A	尺寸B	1		1.68	2	1.27	2.95	3	2.54	4.22	4	3.81	5.49	5	5.08	6.76	6	6.35	8.03	7	7.62	9.30	8	8.89	10.57	9	10.16	11.84	10	11.43	13.11	11	12.70	14.38	12	13.97	15.65	13	15.24	16.92	14	16.51	18.19	15	17.78	19.46	16	19.05	20.73	17	20.32	22.00	18	21.59	23.27	19	22.86	24.54	20	24.13	25.81	21	25.40	27.08	22	26.67	28.35	23	27.94	29.62	24	29.21	30.89	25	30.48	32.16	26	31.75	33.43	27	33.02	34.70	28	34.29	35.97	29	35.56	37.24	30	36.83	38.51	31	38.10	39.78	32	39.37	41.05	33	40.64	42.32	34	41.91	43.59	35	43.18	44.86	36	44.45	46.13	37	45.72	47.40	38	46.99	48.67	39	48.26	49.94	40	49.53	51.21	41	50.80	52.48	42	52.07	53.75	43	53.34	55.02	44	54.61	56.29	45	55.88	57.56	46	57.15	58.83	47	58.42	60.10	48	59.69	61.37	49	60.96	62.64	50	62.23	63.91	A	
Pin数	尺寸A	尺寸B																																																																																																																																																																						
1		1.68																																																																																																																																																																						
2	1.27	2.95																																																																																																																																																																						
3	2.54	4.22																																																																																																																																																																						
4	3.81	5.49																																																																																																																																																																						
5	5.08	6.76																																																																																																																																																																						
6	6.35	8.03																																																																																																																																																																						
7	7.62	9.30																																																																																																																																																																						
8	8.89	10.57																																																																																																																																																																						
9	10.16	11.84																																																																																																																																																																						
10	11.43	13.11																																																																																																																																																																						
11	12.70	14.38																																																																																																																																																																						
12	13.97	15.65																																																																																																																																																																						
13	15.24	16.92																																																																																																																																																																						
14	16.51	18.19																																																																																																																																																																						
15	17.78	19.46																																																																																																																																																																						
16	19.05	20.73																																																																																																																																																																						
17	20.32	22.00																																																																																																																																																																						
18	21.59	23.27																																																																																																																																																																						
19	22.86	24.54																																																																																																																																																																						
20	24.13	25.81																																																																																																																																																																						
21	25.40	27.08																																																																																																																																																																						
22	26.67	28.35																																																																																																																																																																						
23	27.94	29.62																																																																																																																																																																						
24	29.21	30.89																																																																																																																																																																						
25	30.48	32.16																																																																																																																																																																						
26	31.75	33.43																																																																																																																																																																						
27	33.02	34.70																																																																																																																																																																						
28	34.29	35.97																																																																																																																																																																						
29	35.56	37.24																																																																																																																																																																						
30	36.83	38.51																																																																																																																																																																						
31	38.10	39.78																																																																																																																																																																						
32	39.37	41.05																																																																																																																																																																						
33	40.64	42.32																																																																																																																																																																						
34	41.91	43.59																																																																																																																																																																						
35	43.18	44.86																																																																																																																																																																						
36	44.45	46.13																																																																																																																																																																						
37	45.72	47.40																																																																																																																																																																						
38	46.99	48.67																																																																																																																																																																						
39	48.26	49.94																																																																																																																																																																						
40	49.53	51.21																																																																																																																																																																						
41	50.80	52.48																																																																																																																																																																						
42	52.07	53.75																																																																																																																																																																						
43	53.34	55.02																																																																																																																																																																						
44	54.61	56.29																																																																																																																																																																						
45	55.88	57.56																																																																																																																																																																						
46	57.15	58.83																																																																																																																																																																						
47	58.42	60.10																																																																																																																																																																						
48	59.69	61.37																																																																																																																																																																						
49	60.96	62.64																																																																																																																																																																						
50	62.23	63.91																																																																																																																																																																						
B														B																																																																																																																																																										
C														C																																																																																																																																																										
D														D																																																																																																																																																										
E														E																																																																																																																																																										
F														F																																																																																																																																																										
G		<table><tr><td colspan="2">① Series No:</td><td colspan="2">② Pitch:</td><td colspan="2">③ Tail&Mounting Style:</td><td colspan="2">④ No. of Pins:</td><td colspan="2">⑤ Insulator Color:</td></tr><tr><td colspan="2">P=Pin Header</td><td colspan="2">08=0.80</td><td colspan="2">90=Right Angle DIP Type</td><td colspan="2">Single Row Double Row</td><td colspan="2">A:Black B:Brom C:Red</td></tr><tr><td colspan="2">F=Female Header</td><td colspan="2">10=1.00</td><td colspan="2">9S=Straight SMT Type</td><td colspan="2">101=1*1Pin 201=2*1Pin</td><td colspan="2">D:Orange E:Yellow F:Green</td></tr><tr><td colspan="2">B=Box Header</td><td colspan="2">12=1.27</td><td colspan="2">0D=Straight DIP Type</td><td colspan="2">102=1*2Pin 202=2*2Pin</td><td colspan="2">G:Blue H:Violet J:Gray</td></tr><tr><td colspan="2">E=Ejector Header</td><td colspan="2">20=2.00</td><td colspan="2">0S=horizontal SMT Type</td><td colspan="2">11=11 12=12 14=14 20=20 24=24 28=28 32=32 36=36 40=40 44=44 48=48 50=50</td><td colspan="2">K:White P:Light Blue</td></tr><tr><td colspan="2">R=Round Pin</td><td colspan="2">25=2.54</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">39=3.96</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">50=5.08</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">⑥ Material Type:</td><td colspan="2">⑦ Plating Type:</td><td colspan="2">⑧ RoHS Request:</td><td colspan="2">⑨ Customer Code</td><td colspan="2"></td></tr><tr><td colspan="2">A=PBT</td><td colspan="2">0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td colspan="2">0:No Request</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">B-PA46</td><td colspan="2">0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td colspan="2">1:RoHS</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">C-PA6T</td><td colspan="2">0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td colspan="2">2:HF (Halogen Free)</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">D-PA9T</td><td colspan="2">0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">E-LCP</td><td colspan="2">0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>												① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:		P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red		F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green		B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray		E=Ejector Header		20=2.00		0S=horizontal SMT Type		11=11 12=12 14=14 20=20 24=24 28=28 32=32 36=36 40=40 44=44 48=48 50=50		K:White P:Light Blue		R=Round Pin		25=2.54										39=3.96										50=5.08								⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code				A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request						B-PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS						C-PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)						D-PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"								E-LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"										0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"								G				
① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:																																																																																																																																																																
P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red																																																																																																																																																																
F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green																																																																																																																																																																
B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray																																																																																																																																																																
E=Ejector Header		20=2.00		0S=horizontal SMT Type		11=11 12=12 14=14 20=20 24=24 28=28 32=32 36=36 40=40 44=44 48=48 50=50		K:White P:Light Blue																																																																																																																																																																
R=Round Pin		25=2.54																																																																																																																																																																						
		39=3.96																																																																																																																																																																						
		50=5.08																																																																																																																																																																						
⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code																																																																																																																																																																		
A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request																																																																																																																																																																				
B-PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS																																																																																																																																																																				
C-PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)																																																																																																																																																																				
D-PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																																																						
E-LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																																																						
		0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																																																						
H		<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td><td colspan="2">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">LINEAR</td><td colspan="2">APPROVED</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Web: www.dgconne.com Tel: 0769-85337633</td><td colspan="2">KDRH-0009</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ANGLES</td><td colspan="2">DESIGNER</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">0.0±0.25 X° REF±6°</td><td colspan="2">DRAWN</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ENDE4009</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">UNIT: MM 0.00±0.15 X° ±3°</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">TITLE:</td><td colspan="2">REV: A0 SHEET: 1/1</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">SIZE: A4 0.000±0.08 X° X'±2°</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Pitch1.27mm Round Pin, Single Row, Plastic Height 4.1mm, Right Angle Type</td><td colspan="2"></td></tr><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">SIZE: A4</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>																		GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		PART. NO:								LINEAR		APPROVED						Web: www.dgconne.com Tel: 0769-85337633		KDRH-0009								ANGLES		DESIGNER						Email: 2850175986@qq.com Fax: 0769-85392827		DWG. NO:								0.0±0.25 X° REF±6°		DRAWN								ENDE4009								UNIT: MM 0.00±0.15 X° ±3°								TITLE:		REV: A0 SHEET: 1/1								SIZE: A4 0.000±0.08 X° X'±2°								Pitch1.27mm Round Pin, Single Row, Plastic Height 4.1mm, Right Angle Type				REV.		REVISION RECORD		DATE		SIZE: A4												H																												
						GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		PART. NO:																																																																																																																																																								
						LINEAR		APPROVED						Web: www.dgconne.com Tel: 0769-85337633		KDRH-0009																																																																																																																																																								
						ANGLES		DESIGNER						Email: 2850175986@qq.com Fax: 0769-85392827		DWG. NO:																																																																																																																																																								
						0.0±0.25 X° REF±6°		DRAWN								ENDE4009																																																																																																																																																								
						UNIT: MM 0.00±0.15 X° ±3°								TITLE:		REV: A0 SHEET: 1/1																																																																																																																																																								
						SIZE: A4 0.000±0.08 X° X'±2°								Pitch1.27mm Round Pin, Single Row, Plastic Height 4.1mm, Right Angle Type																																																																																																																																																										
REV.		REVISION RECORD		DATE		SIZE: A4																																																																																																																																																																		
1		2		3		4		5		6		7		8																																																																																																																																																										

Specification:
Current Rating : 1AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni