



环保物料



N=Number of Contacts

产品型号	MODEL	KD12EKAM	
材质&电镀	MATERIAL&PLATING	M2.0, 钢, 镀锌 Steel, Zinc Plated	
螺丝	Screw	磷青铜 Phosphor Bronze	
弹片	Reed	-	
焊针	Pin header	-	
塑件	Housing	PA66, UL94V-0	
电气性能	ELECTRICAL	UL	IEC
额定电压	Rated voltage	300V	250V
额定电流	Rated current	8A	7A
接触电阻	Contact resistance	20mΩ	
绝缘电阻	Insulation resistance	500MΩ/1000V	
耐电压	Withstanding voltage	AC1500V/1min	
使用线径	Wire range	28-16AWG 0.5-1.5mm ²	
机械性能	MECHANICAL		
温度范围	Temp. range	-40°C~+105°C	
瞬时温度	Max. soldering	+250°C, 5sec	
扭矩	Torque	0.2N.m 1.7lb.in	
剥线长度	Strip length	6-7mm	

		GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD. 公司网址: www.dgconne.cn 公司电话: 0769-85337633 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827		PART. NO:	KD12EKAM	
				1:1	APPROVED				DWG. NO:	KDTB-0074	
A0	新图面发行	2019.02.18	UNIT: MM	0.00±0.15	DESIGNER		TITLE:		REV:	A0	SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	DRAWN	肖丽娟	2019.02.18	3.50/3.81mm pitch PLUGGABLE TERMINAL BLOCKS			