


环保物料

产品型号	MODEL	KD-30HM
材质&电镀	MATERIAL&PLATING	
螺丝	Screw	M3.0, 钢, 镀镍 Steel, Nickel Plated
端子	Terminal	黄铜, 0.8t 镀锡 Brass, Tin Plated
塑件	Housing	PA66, UL94V-0
电气性能	ELECTRICAL	
额定电压	Rated voltage	300V
额定电流	Rated current	20A
绝缘电阻	Insulation resistance	500MΩ/DC500V
耐电压	Withstanding voltage	AC2000V/1min
使用线径	Wire range	22-14AWG 2.5mm ²
机械性能	MECHANICAL	
温度范围	Temp. range	-40℃~+105℃
扭矩	Torque	0.5N.m 4.4Lb.in



N=Number of Contacts

				GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG ED NEW ENERGY TECHNOLOGY CO., LTD		PART. NO:	
				LINEAR		1:1			公司网址: www.dgconne.cn 公司电话: 0769-85337633		KD-30HM	
				ANGLES		APPROVED			电 邮: 2850175986@qq.com 公司传真: 0769-85392827		DWG. NO:	
AO		新图面发行		0.00±0.15		DESIGNER			TITLE:		KDTB-0206	
REV.		REVISION RECORD		0.000±0.08		DRAWN	肖丽娟	2019.02.25	8.25mm pitch AMERICAN/JAPANESE TERMINAL BLOCKS		REV: AO SHEET: 1/1	